LED STRIPS



		L2SSQ	L2SSS	L2STL	L2STR	L2TRV
		LED SLIM STRIP WITH SQUARE LENS	LED SLIM STRIP WITH ROUND LENS	CONFIGURABLE LED STRIP	LED STRIP	TRI-LEVEL MOTION SENSOR LED STRIP
		3				
Main Selling Features		Sleek and modern square lens design. Slim housing makes it ideal for installation in tight spaces.	Classic round lens design with an economical price point. Slim housing makes it ideal for installation in tight spaces.	Feature-rich and versatile LED strip. Custom built with a multitude of options and configurations to meet the needs and specifications for any application.	Versatile LED strips designed to deliver efficient and high impact illumination. Whether for retrofit or new construction, it's the ideal choice for a variety of commercial and industrial applications.	Integrated tri-level microwave motion sensor, preventing energy loss and increasing energy savings. Perfect solution for applications requiring continuous lighting, such hallways, common areas, parkades and stairwells.
Product Type		Quick Ship	Quick Ship	Made to Order	Quick Ship	Quick Ship
Sizes		4ft & 8ft	2ft, 4ft & 8ft	4ft & 8ft	2ft, 4ft & 8ft	2ft, 4ft & 8ft
End Cap Shape and Width		2 3/8"	2 3/8"	3 3/8"	2 7/8"	27/8"
		17/8"	17/8"	27/8"	27/8"	27/8"
Lumen Output (lm)	Single	-	2ft: 2 620 4ft: 3 900 & 5 888 8ft: 9 825 & 11 790	4ft: 2 530, 3 710, 4 190, 6 019 & 8 954 8ft: 5 117, 7 440, 8 380, 12 038 & 17 908	-	-
	CCT Selectable	4ft: 5 985 - 6 075 8ft: 11 970 - 12 150	-	-	2ft: 2 640 - 2 800 4ft: 7 336 - 7 784	2ft: 2 640 - 2 800 4ft: 7 336 - 7 784
	CCT & Power Selectable	-	-	-	4ft: 3 875 / 4 500 / 5 680 4ft: 5 270 / 5 776 / 6 660 8ft: 9 750 / 11 100 / 12 780	4ft: 3 875 / 4 500 / 5 680 4ft: 5 270 / 5 776 / 6 660 8ft: 9 750 / 11 100 / 12 780
Volts (V)		120-347	120-277 & 120-347	120, 120-277 & 347	120-347	120-347
Color	Single	-	4 000	3 000, 3 500, 4 000 & 5 000	-	-
Temperature (K)	CCT Selectable	4ft & 8ft: 3 500/4 000/5 000	-	-	2ft, 4ft & 8ft: 3 500/4 000/5 000	2ft, 4ft & 8ft: 3 500/4 000/5 000
CRI		80+	80+	80+	80+	80+
Dimming		0-10 V	0-10 V	0-10 V Line Voltage (120 V)	0-10 V	Tri-Level, Bi-Level, On/Off and Daylight Harvesting Capabilities through Integrated Motion Sensor
DLC		Standard & Premium	Standard & Premium	-	Standard & Premium	Standard & Premium
Accessories Included in the Box		Canopy Plate for Junction Box Mounting Brackets	Canopy Plate for Junction Box Mounting Brackets	Canopy Plate for Junction Box	V-Hooks Canopy Plate for Junction Box	V-Hooks Canopy Plate for Junction Box