



A & PS High Intensity



A21 18 W 120 V



A21 20 W 120-277 V



PS30 36W 120-277 V

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	CRI	Beam angle (°)	Life L70 (hrs)	Lumen output (lm)	Case qty (master)
A21 120 V										
68920	A21HO/18W/30K/120/STD	18	E26	120	3 000	90	220	25 000	2 000	12
68921	A21HO/18W/40K/120/STD	18	E26	120	4 000	90	220	25 000	2 000	12
68922	A21HO/18W/50K/120/STD	18	E26	120	5 000	90	220	25 000	2 000	12
A21 120-277 V										
69003	A21HO/20W/30K/120-277/ND/STD	20	E26	120-277	3 000	80	260	25 000	2 600	12
69004	A21HO/20W/40K/120-277/ND/STD	20	E26	120-277	4 000	80	260	25 000	2 600	12
69005	A21HO/20W/50K/120-277/ND/STD	20	E26	120-277	5 000	80	260	25 000	2 600	12
PS30 120-277 V										
68926 ¹	PS30/36W/40K/120-277/EX39/STD	36	EX39	120-277	4 000	80	270	50 000	4 500	6
68927 ¹	PS30/36W/50K/120-277/EX39/STD	36	Ex39	120-277	5 000	80	270	50 000	4 500	6

Traditional Equivalent

LED	CFL	Incandescent	HID
18 W	32 W	150 W	50 W
20 W	32 W - 40 W	150 W - 200W	50 W - 75 W
36 W	55 W	300 W	100 W

Lumen values are derived from photometric testing



damp location enclosed fixture

