



LED Reflector

Allowing you to focus light where it matters, these LED reflectors will not let your colors fade. Choose from many sizes, color temperatures and beam distributions to create the perfect lighting with consistent lamp to lamp color.

Reduce energy consumption and protect all goods and materials that are sensitive to heat and UV emissions.

STANDARD's LED reflectors are ideal for tracks, recessed luminaires and accent lighting in residential, retail, hospitality and commercial applications.



MR11



MR16



GU10

| Order code | Description | Watts (W) | Base | Volts (VAC) | Color temp. (K) | CRI | Life L70 (hrs) | Lumen output (lm) | Beam angle (°) | CBCP (cd) | Traditional equivalent (W) | Case qty (master) |
|--------------------|-------------------------------|-----------|-------|-------------|-----------------|-----|----------------|-------------------|----------------|-----------|----------------------------|-------------------|
| MR11 | | | | | | | | | | | | |
| 64244 ¹ | LED/MR11/4W/30K/38/GU4/ND/STD | 4 | GU4 | 12 | 3 000 | 80 | 25 000 | 260 | 38 | 550 | 30 | 48 |
| MR16 | | | | | | | | | | | | |
| 68263 | MR16/S2/7.5W/27K/25/STD | 7.5 | MR16 | 12 | 2 700 | 90 | 54 000 | 570 | 25 | 3 196 | 75 | 60 |
| 68259 | MR16/S2/7.5W/27K/35/STD | 7.5 | GU5.3 | 12 | 2 700 | 90 | 50 000 | 570 | 35 | 1 908 | 75 | 60 |
| 68264 | MR16/S2/7.5W/30K/25/STD | 7.5 | GU5.3 | 12 | 3 000 | 90 | 54 000 | 570 | 25 | 3 268 | 50 | 60 |
| 68260 | MR16/S2/7.5W/30K/35/STD | 7.5 | GU5.3 | 12 | 3 000 | 90 | 50 000 | 570 | 35 | 1 905 | 75 | 60 |
| 68265 | MR16/S2/7.5W/40K/25/STD | 7.5 | GU5.3 | 12 | 4 000 | 90 | 50 000 | 570 | 25 | 3 613 | 75 | 60 |
| 68261 | MR16/S2/7.5W/40K/35/STD | 7.5 | GU5.3 | 12 | 4 000 | 90 | 50 000 | 570 | 35 | 2 066 | 75 | 60 |
| 68262 | MR16/S2/7.5W/50K/35/STD | 7.5 | GU5.3 | 12 | 5 000 | 90 | 54 000 | 570 | 35 | 2 020 | 50 | 60 |
| GU10 | | | | | | | | | | | | |
| 68252 | GU10/S2/6.5W/27K/25/STD | 6.5 | GU10 | 120 | 2 700 | 90 | 54 000 | 570 | 25 | 1 975 | 75 | 60 |
| 68255 | GU10/S2/6.5W/27K/35/STD | 6.5 | GU10 | 120 | 2 700 | 90 | 54 000 | 570 | 35 | 1 231 | 75 | 60 |
| 68253 | GU10/S2/6.5W/30K/25/STD | 6.5 | GU10 | 120 | 3 000 | 90 | 54 000 | 570 | 25 | 1 975 | 75 | 60 |
| 68256 | GU10/S2/6.5W/30K/35/STD | 6.5 | GU10 | 120 | 3 000 | 90 | 54 000 | 570 | 35 | 1 996 | 50 | 60 |
| 68254 | GU10/S2/6.5W/40K/25/STD | 6.5 | GU10 | 120 | 4 000 | 90 | 54 000 | 570 | 25 | 1 975 | 50 | 60 |
| 68257 | GU10/S2/6.5W/40K/35/STD | 6.5 | GU10 | 120 | 4 000 | 90 | 54 000 | 570 | 35 | 1 231 | 50 | 60 |
| 68258 | GU10/S2/6.5W/50K/35/STD | 6.5 | GU10 | 120 | 5 000 | 90 | 54 000 | 570 | 35 | 1 231 | 50 | 60 |

Lumen values are derived from photometric testing
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com





| Order code | Description | Watts (W) | Base | Volts (VAC) | Color temp. (K) | CRI | Life L70 (hrs) | Lumen output (lm) | Beam angle (°) | CBCP (cd) | Traditional equivalent (W) | Case qty (master) |
|--------------------|-------------------------|-----------|------|-------------|-----------------|-----|----------------|-------------------|----------------|-----------|----------------------------|-------------------|
| PAR16 | | | | | | | | | | | | |
| 63990 | LED/P16/6.5W/30K/38/STD | 6.5 | E26 | 120 | 3 000 | 82 | 40 000 | 582 | 38 | 1 242 | 50 | 24 |
| 63991 | LED/P16/6.5W/40K/38/STD | 6.5 | E26 | 120 | 4 000 | 83 | 40 000 | 635 | 38 | 1 298 | 50 | 24 |
| PAR20 | | | | | | | | | | | | |
| 68218 | P20/S2/7W/27K/25/STD | 7 | E26 | 120 | 2 700 | 90 | 54 000 | 550 | 25 | 3 422 | 50 | 12 |
| 68219 | P20/S2/7W/27K/40/STD | 7 | E26 | 120 | 2 700 | 92 | 54 000 | 550 | 40 | 1 253 | 50 | 12 |
| 68220 | P20/S2/7W/30K/25/STD | 7 | E26 | 120 | 3 000 | 90 | 54 000 | 550 | 25 | 3 572 | 50 | 12 |
| 68221 | P20/S2/7W/30K/40/STD | 7 | E26 | 120 | 3 000 | 90 | 54 000 | 550 | 40 | 1 303 | 50 | 12 |
| 65380 ² | LED/P20H0/7W/30K/35/STD | 7 | E26 | 120 | 3 000 | 82 | 25 000 | 660 | 35 | 1 374 | - | 50 |
| 68222 | P20/S2/7W/40K/25/STD | 7 | E26 | 120 | 4 000 | 90 | 54 000 | 550 | 25 | 3 829 | 50 | 12 |
| 68224 | P20/S2/7W/40K/40/STD | 7 | E26 | 120 | 4 000 | 90 | 54 000 | 550 | 40 | 1 358 | 50 | 12 |
| 68225 | P20/S2/7W/50K/25/STD | 7 | E26 | 120 | 5 000 | 90 | 54 000 | 550 | 25 | 2 350 | 50 | 12 |
| 68226 | P20/S2/7W/50K/40/STD | 7 | E26 | 120 | 5 000 | 90 | 54 000 | 550 | 40 | 1 257 | 50 | 12 |
| PAR30SN | | | | | | | | | | | | |
| 68227 | P30S/S2/12W/27K/25/STD | 10 | E26 | 120 | 2 700 | 90 | 54 000 | 1 050 | 25 | 4 981 | 75 | 6 |
| 68228 | P30S/S2/12W/27K/40/STD | 12 | E26 | 120 | 2 700 | 90 | 50 000 | 1 050 | 40 | 2 337 | 75 | 6 |
| 68229 | P30S/S2/12W/30K/25/STD | 12 | E26 | 120 | 3 000 | 90 | 50 000 | 1 050 | 25 | 5 435 | 75 | 6 |
| 68230 | P30S/S2/12W/30K/40/STD | 10 | E26 | 120 | 3 000 | 90 | 54 000 | 1 050 | 40 | 2 470 | 75 | 6 |
| 68231 | P30S/S2/12W/40K/25/STD | 12 | E26 | 120 | 4 000 | 90 | 54 000 | 1 050 | 25 | 4 450 | 75 | 6 |
| 68232 | P30S/S2/12W/40K/40/STD | 12 | E26 | 120 | 4 000 | 90 | 50 000 | 1 050 | 40 | 2 711 | 75 | 6 |
| 68233 | P30S/S2/12W/50K/25/STD | 12 | E26 | 120 | 5 000 | 75 | 50 000 | 1 050 | 25 | 4 450 | 75 | 6 |
| 68234 | P30S/S2/12W/50K/40/STD | 12 | E26 | 120 | 5 000 | 75 | 50 000 | 1 050 | 40 | 2 100 | 75 | 6 |

Lumen values are derived from photometric testing
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com
² Not Energy Star
³ Consult factory for availability





PAR30LN
S2



PAR38



PAR38
S2

| Order code | Description | Watts (W) | Base | Volts (VAC) | Color temp. (K) | CRI | Life L70 (hrs) | Lumen output (lm) | Beam angle (°) | CBCP (cd) | Traditional equivalent (W) | Case qty (inner/master) |
|----------------|-------------------------|-----------|------|-------------|-----------------|-----|----------------|-------------------|----------------|-----------|----------------------------|-------------------------|
| PAR30LN | | | | | | | | | | | | |
| 68235 | P30L/S2/12W/27K/25/STD | 12 | E26 | 120 | 2 700 | 90 | 50 000 | 1 050 | 25 | 5 240 | 75 | 6 |
| 68236 | P30L/S2/12W/27K/40/STD | 12 | E26 | 120 | 2 700 | 90 | 54 000 | 1 050 | 40 | 2 117 | 75 | 6 |
| 68237 | P30L/S2/12W/30K/25/STD | 12 | E26 | 120 | 3 000 | 90 | 54 000 | 1 050 | 25 | 5 137 | 75 | 6 |
| 68238 | P30L/S2/12W/30K/40/STD | 12 | E26 | 120 | 3 000 | 90 | 50 000 | 1 050 | 40 | 2 639 | 75 | 6 |
| 68239 | P30L/S2/12W/40K/25/STD | 10 | E26 | 120 | 4 000 | 90 | 54 000 | 1 050 | 25 | 5 359 | 75 | 6 |
| 68240 | P30L/S2/12W/40K/40/STD | 12 | E26 | 120 | 4 000 | 90 | 54 000 | 1 050 | 40 | 2 767 | 75 | 6 |
| 68241 | P30L/S2/12W/50K/25/STD | 10 | E26 | 120 | 5 000 | 90 | 54 000 | 1 050 | 25 | 5 473 | 75 | 6 |
| 68242 | P30L/S2/12W/50K/40/STD | 10 | E26 | 120 | 5 000 | 90 | 54 000 | 1 050 | 40 | 2 471 | 75 | 6 |
| PAR38 | | | | | | | | | | | | |
| 68243 | P38/S2/16.5W/27K/25/STD | 15 | E26 | 120 | 2 700 | 90 | 54 000 | 1 370 | 25 | 7 056 | 100 | 1/6 |
| 68244 | P38/S2/16.5W/27K/40/STD | 16.5 | E26 | 120 | 2 700 | 90 | 50 000 | 1 370 | 40 | 2 783 | 120 | 1/6 |
| 68245 | P38/S2/16.5W/30K/25/STD | 16.5 | E26 | 120 | 3 000 | 90 | 50 000 | 1 370 | 25 | 7 354 | 120 | 1/6 |
| 68246 | P38/S2/16.5W/30K/40/STD | 16.5 | E26 | 120 | 3 000 | 90 | 50 000 | 1 370 | 40 | 3 127 | 120 | 1/6 |
| 68247 | P38/S2/16.5W/40K/25/STD | 16.5 | E26 | 120 | 4 000 | 90 | 50 000 | 1 370 | 25 | 6 800 | 120 | 1/6 |
| 68249 | P38/S2/16.5W/40K/40/STD | 16.5 | E26 | 120 | 4 000 | 90 | 54 000 | 1 370 | 40 | 3 237 | 120 | 1/6 |
| 68250 | P38/S2/16.5W/50K/25/STD | 16.5 | E26 | 120 | 5 000 | 90 | 54 000 | 1 370 | 25 | 6 800 | 120 | 1/6 |
| 68251 | P38/S2/16.5W/50K/40/STD | 16.5 | E26 | 120 | 5 000 | 90 | 50 000 | 1 370 | 40 | 2 842 | 120 | 1/6 |

Lumen values are derived from photometric testing
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com
² Not Energy Star
³ Consult factory for availability





| Order code | Description | Watts (W) | Base | Volts (VAC) | Color temp. (K) | CRI | Life L70 (hrs) | Lumen output (lm) | Beam angle (°) | CBCP (cd) | Traditional equivalent (W) | Case qty (inner/master) |
|--------------------|------------------------------|-----------|------|-------------|-------------------------------|-----|----------------|-------------------|----------------|-----------|----------------------------|-------------------------|
| PAR38HO | | | | | | | | | | | | |
| 67918 | P38HO/27W/27K/15/120-277/STD | 27 | E26 | 120-277 | 2 700 | 80 | 50 000 | 2 800 | 15 | 17 684 | 250 | 1/6 |
| 67914 | P38HO/27W/30K/25/120-277/STD | 27 | E26 | 120-277 | 3 000 | 80 | 50 000 | 3 000 | 25 | 7 893 | 250 | 1/6 |
| 67909 | P38HO/27W/30K/40/120-277/STD | 27 | E26 | 120-277 | 3 000 | 80 | 50 000 | 3 000 | 40 | 3 272 | 250 | 1/6 |
| 67915 | P38HO/27W/35K/25/120-277/STD | 27 | E26 | 120-277 | 3 500 | 80 | 50 000 | 3 000 | 25 | 7 893 | 250 | 1/6 |
| 67911 | P38HO/27W/40K/40/120-277/STD | 27 | E26 | 120-277 | 4 000 | 80 | 50 000 | 3 000 | 40 | 3 272 | 250 | 1/6 |
| R20 | | | | | | | | | | | | |
| 64964 ² | LED/R20/S2/6.5W/27K/STD | 6.5 | E26 | 120 | 2 700 | 83 | 25 000 | 525 | 107 | 180 | 50 | 6/24 |
| 69373 ² | R20/6.5W/5CCT/STD | 6.5 | E26 | 120 | 2 700/3 000/3 500/4 000/5 000 | 80 | 25 000 | 525 | 105 | 180 | 50 | 6/24 |
| BR30 | | | | | | | | | | | | |
| 64966 ² | LED/BR30/S2/8W/40K/STD | 8 | E26 | 120 | 4 000 | 82 | 25 000 | 700 | 105 | 240 | 65 | 6/24 |
| 69374 ² | BR30/8W/5CCT/STD | 8 | E26 | 120 | 2 700/3 000/3 500/4 000/5 000 | 80 | 25 000 | 650 | 105 | 235 | 75 | 6/24 |
| BR40 | | | | | | | | | | | | |
| 66032 ² | LED/BR40/S2/16.5W/27K/STD | 16.5 | E26 | 120 | 2 700 | 82 | 25 000 | 1 252 | 103 | 445 | 85 | 6/24 |
| 69375 ² | BR40/12.5W/5CCT/STD | 12.5 | E26 | 120 | 2 700/3 000/3 500/4 000/5 000 | 80 | 25 000 | 1 075 | 105 | 390 | 100 | 6/24 |

Lumen values are derived from photometric testing
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit www.standardpro.com

