



T3 - 78 mm



T3 - 118 mm

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	Life L70 (hrs)	Lumen output (lm)	Beam angle (°)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>G4</b>												
67093 <sup>1 2</sup>	G4/S2/12V/2.3W/30K/STD	2.3	G4	12	3 000	Clear	15 000	230	360	20	Yes	100/1 000
67094 <sup>1 2</sup>	G4/S2/12V/2.3W/40K/STD	2.3	G4	12	4 000	Clear	15 000	230	360	20	Yes	100/1 000
<b>G9</b>												
63444 <sup>2</sup>	LED/G9/3.5W/27K/STD	3.5	G9	120	2 700	Frost	30 000	210	300	20	Yes	50/500
63445 <sup>2</sup>	LED/G9/3.5W/30K/STD	3.5	G9	120	3 000	Frost	30 000	225	300	20	Yes	50/500
63446 <sup>2</sup>	LED/G9/3.5W/40K/STD	3.5	G9	120	4 000	Frost	30 000	245	300	20	Yes	50/500
68990	G9/S2/4W/30K/CL/DESIGN/STD	4	JD	120	3 000	Clear	20 000	350	360	40	Yes	100/200
68991	G9/S2/4W/40K/CL/DESIGN/STD	4	JD	120	4 000	Clear	20 000	350	360	40	Yes	100/200
67941 <sup>3</sup>	G9HO/S3/5W/30K/CL/STD	5	G9	120	3 000	Clear	15 000	480	360	40	Yes	50/500
67942 <sup>3</sup>	G9HO/S3/5W/50K/CL/STD	5	G9	120	5 000	Clear	15 000	480	360	40	Yes	50/500
67943	G9HO/S3/5W/27K/FR/STD	5	G9	120	2 700	Frost	15 000	430	360	35	Yes	50/500
67944	G9HO/S3/5W/30K/FR/STD	5	G9	120	3 000	Frost	15 000	430	360	35	Yes	50/500
67945	G9HO/S3/5W/40K/FR/STD	5	G9	120	4 000	Frost	15 000	430	360	35	Yes	50/500
<b>T3-R7S</b>												
64467	LED/R7S/8W/30K/118/ND/STD	8	R7S	120	3 000	Clear	15 000	650	360	100	No	50/200
69190	R7S/S2/6W/30K/78/STD	6	R7S	120	3 000	Clear	15 000	550	360	40	Yes	50/200
69191	R7S/S2/6W/40K/78/STD	6	R7S	120	4 000	Clear	15 000	580	360	40	Yes	50/200

Lumen values are derived from photometric testing  
 For a complete list of compatible dimmers, please visit [www.standardpro.com](http://www.standardpro.com)  
<sup>3</sup> If used in totally enclosed luminaire life hours may be reduced by 50%

