

# EXTRUDED ALUMINUM

NRCan C860 Registered LED 120/347 V AC Input



Approvals:

CSA Certified to C22.2 #141.15, C860

## DESCRIPTION

The clean lines of the SLEXX/SLSRX series of commercial extruded aluminum signs present a fully modern appearance. The extruded aluminum provides for a rigid, durable and lightweight sign. Available in AC only, AC/DC and internally self-powered versions.

### CIRCUITRY - AC & AC/DC

- LED ultra bright light source
- 120/347 V AC Input, field selectable
- 1.9W power consumption single or double face
- Emergency DC wattages as follows:

**EXIT: 6 V DC** = 1.0W **12 V DC** = 1.4W **24 V DC** = 3.5W **SORTIE:** 6 **V DC** = 1.3W **12 V DC** = 1.7W **24 V DC** = 3.2W

# CIRCUITRY - SELF-POWERED

- LED ultra bright light source
- 120/347 V AC Input, field selectable
- 4W power consumption single or double face
- High-performance, sealed Ni-Cad battery
- 90 minutes emergency duration (standard)
- Solid state transfer and battery charger





quick ship

## MECHANICAL

- Extruded aluminum construction
- Slide in/out captive faceplate(s) and backplate for rapid and simplified installation
- Snap out directional chevrons/arrows
- Universal spider knockout pattern stamped into backplate for junction box mounting
- · Universal models include ceiling or end mount, field installable canopy kit c/w spider plate
- · White powder coat finish standard, other finishes and colors optional

#### DIMENSIONS

5.63"	4.38" 7 0.38"	5.63"
«SORTIE»	7.5"	« EXIT »
18.5"	→ <sub>2"</sub> ⊢	13"

## ORDERING GUIDE

	C		_	-	•
Series	Approval	Nbr of faces	Color	DC Voltage*	Options†
SLEXX- (Exit) SLSRX -(Sortie)	C - C860 Certified	1 - Single face 2 - Double face	WH - White BK - Black GY - Grey BA - Brushed aluminum SP - Custom color (specify)	UDC - 6, 12, 24V universal DC IB - Self powered for 90 min.	VS, WG**, LG, OP, K5

<sup>†</sup> For detailed options descriptions, please consult the options page.

QUICK SHIP: Not all products are Quick Ship. To view our Quick Ship qualified products, please consult our Quick Ship Product Guide at stanprols.com/quick-ship-product-guide. Product availability is subject to change without notice. Please contact your Stanpro customer service representative to confirm inventory levels at time of order



If AC only is required, select the UDC option and do not connect the DC wires when installing.