# SLEXY-SLSRY

# **HAZARDOUS LOCATION**

Class I, Division 1, Groups C & D, Zone 1 & 2, Groups IIA & IIB AC, AC/DC 120/347VAC Input

The SLEXY and SLSRY series of hazardous location exit signs is designed to meet and exceed the most stringent code requirements. The housings are made from copper free, heavy-duty die cast aluminum. The frame and faceplate(s) are manufactured in heavy gauge steel with a white, powder coating finish. The signs can be specified to suit a variety of mounting options including ceiling, wall and pendant mount.

## FEATURES AND SPECIFICATIONS

- Circuitry AC & AC/DC
  - LED ultra bright light source
  - Input voltages 120/347VAC
  - Emergency back-up votage: 6V, 12V or 24VDC

#### • Mechanical

- Die cast, copper free aluminum, white or raw aluminum finish
- Steel exit sign, white powder coat finish standard
- Snap out directional chevrons/arrows
- Wiring pre-pulled through fixture
- Wall and ceiling models c/w integrated die cast junction box
- Junction box c/w oversized integral mounting holes and tapped and plugged rigid holes
- Comes with a transfer panel for hazardous locations (for AC/DC versions)
- TSFN enclosure must be installed/located outside the classified hazardous location


7-3/4


- Temperature code: T6

## **MOUNTING & DIMENSIONS**



CEILING





7.66"



- CSA Certified to C22.2 #137
- CSA Certified to C22.2 #141-15
- CSA Certified to C860-11

17-3/8

WALL

- Class I, Division 1, Groups C & D
- Class I, Zone 1 & 2, Groups IIA & IIB











hazardous location



#### **OVERVIEW**

Light source	LED
Input voltage	120/347VAC
DC input voltage	6VDC, 12VDC, or 24VDC

7-3/4"

6

7.66"





# **SLEXY-SLSRY**

#### **ORDERING GUIDE**

		1	1	CD			/
Series	Nbr of faces	Class	Div.	Group	DC Voltage	Mounting	Options <sup>†</sup>
SLEXY - Exit	1 - Single face	1	1	С	Blank - AC only	CM - Ceiling mount	<b>OP -</b> Special wording or graphic
SLSRY - Sortie	2 - Double face			D	<b>06 -</b> 6V	PM - Pendant mount	
					12 - 12V	WM - Wall mount	
					<b>24 -</b> 24V		

<sup>+</sup> For detailed options descriptions, please consult the options page.

## Comments

All products are subject to change or may be discontinued any time without notice.

