

Neodymium



MOL: 1 13/16 in. (46 mm)
Ø 2 in. (51 mm)

MR16 (GU5.3)



MOL: 3 21/32 in. (46 mm)
Ø 3 3/4 in. (95 mm)

PAR30

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
MR16											
60871	H50MR16/FL/N/CG/2M/GU5.3/12V/STD	50	GU5.3	12	550	2 000	Neo.	38	Flood	1 400	12/120
PAR30											
58360 ²	H75PAR30/FL/N/2M/130V/STD	75	E26	130	1 000	2 000	Neo.	30	Flood	N/A	1/15

ICE



MOL: 2 5/32 in. (45 mm)
Ø 2 in. (51 mm)

ES16 (GU10)



MOL: 4 13/16 in. (95 mm)
Ø 3 3/4 in. (95 mm)

PAR30LN

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
ES16										
55051 ¹	H35GU10/CG/2.5M/120V/STD ICE	35	GU10	120	280	2 500	40	Flood	600	10/200
55038 ¹	H50GU10/CG/2.5M/120V/STD ICE	50	GU10	120	500	2 500	40	Flood	840	10/200
55037 ¹	H50GU10/CG/2.5M/130V/STD ICE	50	GU10	130	375	2 500	40	Flood	840	10/200
PAR30LN										
50188 ²	H50PAR30/LN/FL/5M/130V/STD ICE	50	E26	130	450	5 000	N/A	Flood	N/A	1/15

¹ This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.
² This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

UNI-FROST™



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 2.5/32 in. (45 mm)
Ø 2 in. (51 mm)

ES16 (GU10)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Colour/Finish	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
MR16 - Cover Glass											
57211 ¹	H50MR16/CG/4M/GU5.3/12V/STD UFR	50	GU5.3	12	750	4 000	Frost	N/A	N/A	N/A	10/200
ES16 - Cover Glass											
57212 ^{1,2}	H35GU10/CG/2.5M/120V/STD UFR	35	GU10	120	330	2 500	Frost	N/A	N/A	N/A	10/200
57213 ^{1,2}	H50GU10/CG/2.5M/120V/STD UFR	50	GU10	120	520	2 500	Frost	N/A	N/A	N/A	10/200
57801 ^{1,2}	H50GU10/CG/3M/130V/STD UFR	50	GU10	130	390	3 000	Frost	N/A	N/A	N/A	10/200

Colored



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 3.9/32 in. (83 mm)
Ø 2.5 in. (63.5 mm)

PAR20



MOL: 3.21/32 in. (83 mm)
Ø 3.3/4 in. (85 mm)

PAR30



MOL: 5.5/16 in. (135 mm)
Ø 4.3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Color	Beam angle (°)	Beam spread	Case qty (inner/master)
MR16									
55066	H50MR16/FL/R/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Red	38	Flood	10/200
55067	H50MR16/FL/Y/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Yellow	38	Flood	10/200
PAR20									
55002	H35PAR20/NFL/G/2M/130V/STD	35	E26	130	2 000	Green	30	Narrow Flood	1/15
55004	H35PAR20/NFL/B/2M/130V/STD	35	E26	130	2 000	Blue	30	Narrow Flood	1/15
PAR30									
55006	H50PAR30/FL/R/2M/130V/STD	50	E26	130	2 000	Red	30	Flood	1/15
55007	H50PAR30/FL/G/2M/130V/STD	50	E26	130	2 000	Green	30	Flood	1/15
55008	H50PAR30/FL/Y/2M/130V/STD	50	E26	130	2 000	Yellow	30	Flood	1/15
PAR38									
51182	H90PAR38/FL/G/2M/MS/130V/STD	90	E26	130	2 000	Green	30	Flood	1/15
51184	H90PAR38/FL/Y/2M/MS/130V/STD	90	E26	130	2 000	Yellow	30	Flood	1/15

¹This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.