

UNI-FROST™



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 2.5/32 in. (45 mm)
Ø 2 in. (51 mm)

ES16 (GU10)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Colour/Finish	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (inner/master)
MR16 - Cover Glass											
57211 ¹	H50MR16/CG/4M/GU5.3/12V/STD UFR	50	GU5.3	12	750	4 000	Frost	N/A	N/A	N/A	10/200
ES16 - Cover Glass											
57212 ^{1,2}	H35GU10/CG/2.5M/120V/STD UFR	35	GU10	120	330	2 500	Frost	N/A	N/A	N/A	10/200
57213 ^{1,2}	H50GU10/CG/2.5M/120V/STD UFR	50	GU10	120	520	2 500	Frost	N/A	N/A	N/A	10/200
57801 ^{1,2}	H50GU10/CG/3M/130V/STD UFR	50	GU10	130	390	3 000	Frost	N/A	N/A	N/A	10/200

Colored



MOL: 1.25/32 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 3.9/32 in. (83 mm)
Ø 2.5 in. (63.5 mm)

PAR20



MOL: 3.21/32 in. (83 mm)
Ø 3.3/4 in. (85 mm)

PAR30




MOL: 5.5/16 in. (135 mm)
Ø 4.3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Average life (hrs)	Color	Beam angle (°)	Beam spread	Case qty (inner/master)
MR16									
55066	H50MR16/FL/R/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Red	38	Flood	10/200
55067	H50MR16/FL/Y/CG/4M/GX5.3/12V/STD	50	GX5.3	12	4 000	Yellow	38	Flood	10/200
PAR20									
55002	H35PAR20/NFL/G/2M/130V/STD	35	E26	130	2 000	Green	30	Narrow Flood	1/15
55004	H35PAR20/NFL/B/2M/130V/STD	35	E26	130	2 000	Blue	30	Narrow Flood	1/15
PAR30									
55006	H50PAR30/FL/R/2M/130V/STD	50	E26	130	2 000	Red	30	Flood	1/15
55007	H50PAR30/FL/G/2M/130V/STD	50	E26	130	2 000	Green	30	Flood	1/15
55008	H50PAR30/FL/Y/2M/130V/STD	50	E26	130	2 000	Yellow	30	Flood	1/15
PAR38									
51182	H90PAR38/FL/G/2M/MS/130V/STD	90	E26	130	2 000	Green	30	Flood	1/15
51184	H90PAR38/FL/Y/2M/MS/130V/STD	90	E26	130	2 000	Yellow	30	Flood	1/15

¹This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.

MR11 & MR16



MOL: 1.378 in. (35 mm)
Ø 1.376 in. (35 mm)

MR11 (G4)



MOL: 1.25132 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GX5.3)



MOL: 2.562 in. (65 mm)
Ø 2 in. (51 mm)

MR16 (E26)



MOL: 1.25132 in. (45 mm)
Ø 2 in. (51 mm)

MR16 (GU10)

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	Case qty (inner/master)
MR11 - Cover Glass										
55054	H5MR11/NSP/CG/2M/G4/12V/STD	5	G4	12	45	2 000	2 900	10	Narrow Spot	12/120
67901	H20MR11/MFL/CG/2M/GU4/12V/FTD	20	GU4	12	200	2 000	2 800	36	Flood	10/250
50899	H35MR11/MFL/CG/2M/G4/12V/FTH STD	35	G4	12	345	2 000	2 900	28	Flood	10/200
67899	H35MR11/NFL/CG/GU4/12V/FTF	35	GU4	12	345	2 000	2 800	24	Narrow Flood	10/250
MR11 - Open										
50894	H20MR11/NSP/AX/G4/12V/FTB STD	20	G4	12	200	2 000	2 900	11	Narrow Spot	12/120
50898	H35MR11/MFL/AX/G4/12V/FTH STD	35	G4	12	345	2 000	2 900	30	Flood	12/120
MR16 - Cover Glass										
51134 ¹	H20MR16/FL/CG/4M/GX5.3/12V/BAB STD	20	GX5.3	12	260	4 000	2 950	38	Flood	10/200
50892 ¹	H35MR16/FL/CG/4M/GX5.3/12V/FMW STD	35	GX5.3	12	530	4 000	3 000	38	Flood	10/200
50893	H50MR16/FL/CG/4M/GX5.3/12V/EXN STD	50	GX5.3	12	850	4 000	3 050	38	Flood	10/200
MR16 - Cover Glass - Line Voltage										
55570 ^{1,2}	H35MR16/FL/CG/2M/E26/120V/STD	35	E26	120	240	2 000	2 800	38	Flood	10/200
55569 ^{1,2}	H50MR16/FL/CG/2M/E26/120V/STD	50	E26	120	420	2 000	2 800	38	Flood	10/200
59590 ^{1,2}	H35MR16/FL/CG/E26/130V/STD	35	E26	130	180	2 500	2 800	38	Flood	10/200
59589 ^{1,2}	H50MR16/FL/CG/E26/130V/STD	50	E26	130	315	2 500	2 800	38	Flood	10/200
MR16 (GU10)										
55034 ¹	H20GU10/NFL/CG/2.5M/120V/STD	20	GU10	120	120	2 500	2 800	25	Narrow Flood	10/200
55033 ¹	H35GU10/NFL/CG/2.5M/120V/STD	35	GU10	120	280	2 500	2 800	25	Narrow Flood	10/200
10437 ¹	H50GU10/NFL/CG/2.5M/120V/STD	50	GU10	120	375	2 500	2 800	25	Narrow Flood	10/200
55035	H50GU10/NFL/2M/CG/120V/ HS	50	GU10	120	N/A	2 000	2 800	25	Narrow Flood	10/200
10438 ¹	H50GU10/NFL/CG/3M/130V/STD	50	GU10	130	500	3 000	2 800	25	Narrow Flood	10/200
MR16 - Open										
51066 ¹	H20MR16/FL/4M/GX5.3/12V/BAB STD	20	GX5.3	12	260	4 000	2 950	36	Flood	10/200
50888 ¹	H35MR16/FL/4M/GX5.3/12V/FMW STD	35	GX5.3	12	530	4 000	3 000	38	Flood	10/200
50890	H50MR16/NFL/4M/GX5.3/12V/EXZ STD	50	GX5.3	12	850	4 000	3 050	24	Narrow Flood	10/200
50891	H50MR16/FL/4M/GX5.3/12V/EXN STD	50	GX5.3	12	850	4 000	3 050	38	Flood	10/200

¹This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.

Energy Saving PAR



MOL: 4 11/16 in. (119 mm)
Ø 3 3/4 in. (95 mm)

PAR30LN



MOL: 5 5/16 in. (132 mm)
Ø 4 15/16 in. (120 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Finish	Operating position	Beam angle (°)	Beam spread	CBCP (cd)	Incan. equiv. (W)	Case qty (master)
PAR30LN													
63800	H35/PAR30LN/ECO/FL/120V/STD	35	E26	120	500	2 000	Silver	Universal	30	Flood	900	50	15
PAR38													
63802 ¹	H60/PAR38/ECO/FL/120V/STD	60	E26	120	1 070	1 500	Silver	Universal	30	Flood	1 100	75	15



¹ This product is no longer available in Ontario as per Energy Efficiency Regulations.



ACCUBEAM

ACCUBEAM lamps use a reflector design that forms the light beam before it reaches the lens. The corrugated reflector allows for greater light concentration at the center of the beam providing a light output that is comparable to conventional halogens, while using less wattage. ACCUBEAM was designed to deliver a smooth, precise beam pattern and allows for even light distribution; without hot spots or striations.



MOL: 5.5/16 in. (138 mm)
Ø 4.3/4 in. (121 mm)

PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Beam angle (°)	Beam spread	Case qty (master)
PAR38									
50066 ¹	H45PAR38/SP/5M/130V/STD ACC	45	E26	130	390	5 000	10	Spot	15
50041 ¹	H45PAR38/FL/5M/130V/STD ACC	45	E26	130	390	5 000	30	Flood	15

¹ This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.



Reflector



PAR16



PAR20



PAR56

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	Case qty (master)
PAR16										
50974 ¹	H40PAR16/NFL/2.5M/130V/STD	40	E26	130	400	2 500	2 800	30	Narrow Flood	15
PAR20										
69248	H35PAR20/NFL/2.5M/130V/STD S2	35	E26	130	235	5 000	2 800	28	Narrow Flood	15
PAR56										
43495	Q500PAR56MFL	500	GX16d	120	8 000	4 000	2 950	42	Flood	6
43496	Q500PAR56WFL	500	GX16d	120	8 000	4 000	2 950	66	Wide Flood	6



PAR38

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Beam angle (°)	Beam spread	CBCP (cd)	Case qty (master)
PAR38											
10146 ²	H60PAR38/CLB/5M/MS/130V/STD	60	E26	130	800	5 000	2 900	36	Flood	1 700	15

¹ This product is affected by provincial Energy Efficiency Regulations in British Columbia. Note that it will remain available until stock is depleted.
² This product is no longer manufactured as per Energy Efficiency Regulations. Note that it will remain available until stock is depleted.

ALR

ALR lamps are halogen aluminium reflector lamps. They are a lightweight and compact light source which are mainly used in display lighting, accent lighting, task lighting and in elevators.



Hgt. 1 17/32 in. (89 mm)
 D 1 1/2 in. (68 mm)

ALR12

Order code	Description	Watts (W)	Base	Volts (V)	Lumen output (lm)	Average life (hrs)	Color temp. (K)	Finish	Beam angle (°)	Beam spread	Case qty (inner/master)
ALR12 - Cover Glass											
55062	20ALR12/F/FL/BA15d/12V/GBF STD	20	BA15d	12	750	2 000	3 000	Frost	32	Flood	20/100

