

# Specialty



MOL.: 4 1/2 in. (114 mm)  
 Ø 25/32 in. (20 mm)  
 LCL.: 2 5/16 in. (69 mm)

T6



MOL.: 5 3/16 in. (132 mm)  
 Ø 29/32 in. (23 mm)  
 LCL.: 2 13/16 in. (61 mm)

T7



MOL.: 11 1/2 in. (292 mm)  
 Ø 4 19/25 in. (121 mm)  
 LCL.: 7 in. (178 mm)

ED37

Order code	Description	Shape	Base	ANSI code	Color temp. (K)	Lumen output (lm)	Mean lumens (lm)	Average life (hrs)	CRI	Operating position	Finish	Luminaire	Case qty (master)
<b>70 watts</b>													
57975	MH-DE 70W/UVS/4K STD	T6	R7s	M85/E	4 200	5 500	3 600	10 000	65	HOR±45°	Clear	E	25
68869	MH-DE 70W/UVS/3K STD	T6	R7s	M85/E	3 000	5 500	4 250	6 000	65	HOR±45°	Clear	E	144
<b>150 watts</b>													
59141	MH-DE 150W/UVS/3K STD	T7	R7s	M81/E	3 000	11 250	8 400	10 000	65	HOR±45°	Clear	E	25
<b>360 watts</b>													
68526	MPI360W/BU/EM STD	ED37	EX39	M165/M59/O	4 200	36 000	28 800	20 000	65	BU±15°	Clear	O	6

# Ceramic Metal Halide



35W: MOL.: 3 15/16 in. (100 mm)  
 70W: MOL.: 3 3/4 in. (96 mm)  
 Ø 3/4 in. (19 mm)  
 LCL.: 2 7/32 in. (66 mm)

T6



MOL.: 4 13/16 in. (122 mm)  
 Ø 3 3/4 in. (95 mm)

PAR30LN



MOL.: 3 11/32 in. (85 mm)  
 LCL.: 2 1/16 in. (52 mm)

T4.5

Order code	Description	Shape	Base	Color temp. (K)	Average life (h)	Initial lumens (lm)	Mean lumens (lm)	CRI	Operating position	Finish	Luminaire	Case qty (master)
<b>35 watts</b>												
59993	CMH35PAR30LN/830/FL/STD	PAR30LN	E26	3 000	8 000	2 200	1 804	80	U	Clear	O	6
68875	CMT35/U/830/G12/STD	T6	G12	3 000	10 000	3 400	2 890	80	U	Clear	E	12
69171	CMT35/U/830/G8.5/STD	T4.5	G8.5	3 000	10 000	3 400	2 890	85	U	Clear	E	12
<b>70 watts</b>												
68876	CMT70/U/830/G12/STD	T6	G12	3 000	15 000	7 000	5 950	85	U	Clear	U	12

O = Open rated for indoor fixtures E = Enclosed rated for indoor or outdoor fixtures  
 Note: Lamp description containing UVS have the UV Stop feature.