

Réflecteur



MOL : 3 3/4 in. (95 mm)
Ø 2 15/32 in. (63 mm)

PAR20



MOL : 4 7/8 in. (124 mm)
Ø 2 7/16 in. (62 mm)

R20

| Code de commande | Description | Watts (W) | Culot | Couleur temp. (K) | Flux lumineux (lm) | Vie moyenne (h) | IRC | Équivalent incandescente (W) | Qté caisse (int./ext.) |
|--------------------|-----------------------|-----------|-------|-------------------|--------------------|-----------------|-----|------------------------------|------------------------|
| PAR20 | | | | | | | | | |
| 14100 ¹ | CF9/27K/PAR20/E26/STD | 9 | E26 | 2 700 | 300 | 8 000 | 82 | 50 | 6/48 |
| 14102 ¹ | CF9/35K/PAR20/E26/STD | 9 | E26 | 3 500 | 300 | 8 000 | 82 | 50 | 6/48 |
| R20 | | | | | | | | | |
| 14162 | CF11/27K/R20/E26/STD | 11 | E26 | 2 700 | 350 | 8 000 | 82 | 50 | 6/48 |

Cathode froide



MOL : 4 17/32 in. (115 mm)
Ø 2 3/8 in. (60 mm)

A19

| Code de commande | Description | Watts (W) | Culot | Couleur temp. (K) | Flux lumineux (lm) | Vie moyenne (h) | Couleur | IRC | Équivalent incandescente (W) | Qté caisse (int./ext.) |
|------------------|-------------------------|-----------|-------|-------------------|--------------------|-----------------|---------|-----|------------------------------|------------------------|
| A19 | | | | | | | | | | |
| 58427 | CCFL8/F/A19/25M/E26/STD | 8 | E26 | 2 700 | 320 | 25 000 | Givrée | 82 | 35-40 | 1/48 |



¹ Convient aux emplacement extérieur (culot vers le haut)