

T12

Code de commande	Description	Watts (W)	Culot	Couleur temp. (K)	Durée de vie DP/DPR (3 h)	Flux lumineux (lm)	Lumens moyens (lm)	IRC	Longueur nominale po (mm)	Efficacité (lm/W)	Qté caisse (int./ext.)
Série 900 Ø 1 1/2 po (38 mm)											
64251	F40T12/41K/9/RS/G13/STD	40	G13	4 100	24 000	2 500	2 500	90	48 (1 220)	63	30
64252	F40T12/50K/9/RS/G13/STD	40	G13	5 000	24 000	2 250	2 250	90	48 (1 220)	56	30
64253	F40T12/65K/9/RS/G13/STD	40	G13	6 500	24 000	2 250	2 250	90	48 (1 220)	56	30

Circulaire & en forme de U

Code de commande	Description	Watts (W)	Culot	Couleur temp. (K)	Flux lumineux (lm)	Lumens moyens (lm)	Durée de vie DI (3 h)	IRC	Longueur nominale po (mm)	Efficacité (lm/W)	Qté caisse (ext.)
Circulaire Ø 1 3/16 po (30 mm)											
58984	FC6T9/CW/RS/4P/STD	20	G10q-4	4 100	890	850	10 000	82	7 (165)	45	12
58983	FC8T9/CW/RS/4P/STD	22	G10q-4	4 100	1 350	1 280	10 000	82	8 (210)	61	24
58982	FC8T9/DL/RS/4P/STD	22	G10q-4	6 500	1 210	1 150	10 000	82	8 (210)	55	24
58986	FC12T9/CW/RS/4P/STD	32	G10q-4	4 100	2 300	2 185	10 000	82	12 (305)	72	24
58987	FC12T9/DL/RS/4P/STD	32	G10q-4	6 500	2 000	1 900	10 000	82	12 (305)	63	12
58988	FC16T9/CW/RS/4P/STD	40	G10q-4	4 100	3 150	3 000	10 000	82	16 (406)	79	12
En forme de U Ø 1 po (26 mm)											
T8 série 800											
58698	FB31T8/35K/8/U1/RS/G13/STD	31	G13	3 500	2 750	2 610	24 000	82	22.5 (572)	89	20
65500	FB32T8/30K/8/U6/RS/G13/STD ESV	28	G13	3 000	2 800	2 772	20 000	85	22.5 (572)	85	20
65501	FB32T8/35K/8/U6/RS/G13/STD ESV	31	G13	3 000	2 800	2 825	20 000	85	22.5 (572)	85	20
65502	FB32T8/41K/8/U6/RS/G13/STD ESV	32	G13	4 100	2 800	2 550	20 000	85	22.5 (572)	88	20
65503	FB32T8/50K/8/U6/RS/G13/STD ESV	32	G13	5 000	2 750	2 500	20 000	86	22.5 (572)	86	20
T8 série 900 Ø 1 1/2 po (38 mm)											
64255	FB40T12/41K/9/U6/RS/G13/STD	40	G13	4 100	2 500	2 500	24 000	90	22.6 (574)	63	12
64256	FB40T12/65K/9/U6/RS/G13/STD	40	G13	6 500	2 500	2 250	24 000	90	22.6 (574)	56	12