

Spécialité



T6

MOL.: 4 1/2 in. (114 mm)
 Ø 25/32 in. (20 mm)
 LCL.: 2 5/16 in. (59 mm)



T7

MOL.: 5 3/16 in. (132 mm)
 Ø 29/32 in. (23 mm)
 LCL.: 2 13/16 in. (61 mm)



ED37

MOL.: 11 1/2 in. (292 mm)
 Ø 4 19/25 in. (121 mm)
 LCL.: 7 in. (178 mm)

| Code de commande | Description | Forme | Culot | Code ANSI | Couleur temp. (K) | Flux lumineux (lm) | Lumens moyens (lm) | Vie moyenne (h) | IRC | Position de fonc. | Finition | Luminaire | Qté caisse (ext.) |
|------------------|-----------------------|-------|-------|------------|-------------------|--------------------|--------------------|-----------------|-----|-------------------|----------|-----------|-------------------|
| 70 watts | | | | | | | | | | | | | |
| 57975 | MH-DE 70W/UVS/4K STD | T6 | R7s | M85/E | 4 200 | 5 500 | 3 600 | 10 000 | 65 | HOR±45° | Claire | E | 25 |
| 68869 | MH-DE 70W/UVS/3K STD | T6 | R7s | M85/E | 3 000 | 5 500 | 4 250 | 6 000 | 65 | HOR±45° | Claire | E | 144 |
| 150 watts | | | | | | | | | | | | | |
| 59141 | MH-DE 150W/UVS/3K STD | T7 | R7s | M81/E | 3 000 | 11 250 | 8 400 | 10 000 | 65 | HOR±45° | Claire | E | 25 |
| 360 watts | | | | | | | | | | | | | |
| 68526 | MPI360W/BU/EM STD | ED37 | EX39 | M165/M59/O | 4 200 | 36 000 | 28 800 | 20 000 | 65 | BU±15° | Clear | O | 6 |

Halogénure métallique en céramique



T6

35W: MOL.: 3 15/16 in. (100 mm)
 70W: MOL.: 3 3/4 in. (96 mm)
 Ø 3/4 in. (19 mm)
 LCL.: 2 7/32 in. (56 mm)



PAR30LN

MOL.: 4 13/16 in. (122 mm)
 Ø 3 3/4 in. (95 mm)



T4.5

MOL.: 3 11/32 in. (85 mm)
 LCL.: 2 1/16 in. (52 mm)

| Code de commande | Description | Forme | Culot | Couleur temp. (K) | Vie moyenne (h) | Lumens initiaux (lm) | Lumens moyens (lm) | IRC | Position de fonc. | Finition | Luminaire | Qté caisse (ext.) |
|------------------|-------------------------|---------|-------|-------------------|-----------------|----------------------|--------------------|-----|-------------------|----------|-----------|-------------------|
| 35 watts | | | | | | | | | | | | |
| 59993 | CMH35PAR30LN/830/FL/STD | PAR30LN | E26 | 3 000 | 8 000 | 2 200 | 1 804 | 80 | U | Claire | O | 6 |
| 68875 | CMT35/U/830/G12/STD | T6 | G12 | 3 000 | 10 000 | 3 400 | 2 890 | 80 | U | Claire | E | 12 |
| 69171 | CMT35/U/830/G8.5/STD | T4.5 | G8.5 | 3 000 | 10 000 | 3 400 | 2 890 | 85 | U | Clear | E | 12 |
| 70 watts | | | | | | | | | | | | |
| 68876 | CMT70/U/830/G12/STD | T6 | G12 | 3 000 | 15 000 | 7 000 | 5 950 | 85 | U | Claire | U | 12 |

O = Luminaire intérieur ouvert. E = Luminaire fermé pour intérieur ou extérieur
 Note : Si la Description de la lampe contient UVS, la lampe possède la caractéristique anti-UV.