

Traditional Recessed

We have taken our years of lighting expertise and incorporated it into our line of high quality recessed fixtures designed with ease of installation and versatile lighting options in mind. Recessed fixtures provide convenient unobtrusive general lighting for residential and commercial applications, and with Stanpro's extensive assortment of trims and housings, you can create an unparalleled look. Our wide varieties of trims suit all applications and complement every decor. Paired with Canada's largest selection of LED lamps you will be sure to find the best combination for all your lighting needs.

3" Housing



Order code	Model number	Opening diameter (in.)	Volts (VAC)	Socket	Case qty (master)
Remodeler - IC / Non-IC					
63230 ¹	RF3in/REMOD/IC/GU10/STD	3	120	GU10	6

3" Trims

Compatible Lamps (MR16 GU10)



Order code	Model number	Finish	Rotation angle (°)	Case qty (inner/master)
Recessed Die-Cast				
62700 ²	RF3/TRIM/DIECAST.REC/CHR/STD	Chrome	N/A	6/24
62701 ²	RF3/TRIM/DIECAST.REC/SAT.CHR/STD	Satin chrome	N/A	6/24
62699 ²	RF3/TRIM/DIECAST.REC/WH/STD	White	N/A	6/24
Gimbal				
62711 ²	RF3/TRIM/GMB/CHR/STD	Chrome	35	6/24
62715	RF3/TRIM/GMB/SAT.CHR/STD	Satin chrome	35	6/24
62703 ²	RF3/TRIM/GMB/WH/STD	White	35	6/24
62719 ²	RF3/TRIM/GMB/BLK/STD	Black	35	6/24
62707 ²	RF3/TRIM/GMB/ORB/STD	Oil rubbed bronze	35	6/24
Gimbal				
62710 ²	RF3/TRIM/SQR/GMB/CHR/STD	Chrome	35	6/24
62714 ²	RF3/TRIM/SQR/GMB/SAT.CHR/STD	Satin chrome	35	6/24
62702 ²	RF3/TRIM/SQR/GMB/WH/STD	White	35	6/24

Accessories

Order code	Model number	Opening diameter (in.)	Type	Case qty (master)
66047	ACC/MPLATE/3.25IN/SQR/STD	3 ¼	Square mounting plates	96
66054	ACC/MPLATE/3.25IN/ADJ/STD	3 ¼	Adjustable mounting plates	24
62673	ACC/MPLATE/3.25IN/HANG.BARS/STD	3 ¼	Mounting plates with hanger bars	20
66142	ACC/3/VAPOR BARRIER/STD	3 5/8	Vapor barrier extender	50



For complete warranty information, please visit www.standardpro.com
¹ This housing is rated for both insulated ceilings (IC) and non-insulated ceilings (non-IC), however, only to be used with an LED lamp in an IC application
² Safety glass included, only to be installed with an open style lamp. Not suitable for LED technology

6 damp location

¹
7w maximum per lamp
50w maximum per lamp
1 yr warranty

