

Choose the right LED Downlight

All of our LED downlights are available in quick ship and certified Energy Star.



		LPDL - Low profile downlight		Swivel	Gimbal		Retro	Vivio	Presto	CDU	CDU Gen 2
		Choice	Stanpro	Choice	Gimbal 7W	Gimbal HO					
Main selling features		Ultra slim recessed downlight, less than 1" thick, perfect for shallow or constraint ceiling spaces		Directional downlight which can highlight specific zones with 360° rotation and up to 90° tilt	Small aperture and highly versatile design with directional light output	Outstanding performance, small aperture and recessed design with directional light output	Retrofit solution with E26 screw-in adaptor for existing recessed cans, easy installation	Dual installation offering both retrofit option or mounted directly into a 4" junction box	Quick installation with LED driver mounted directly on top of the light engine	All-in-one commercial downlight with integrated 3 CCT and 4 power selectable	All-in-one commercial downlight with integrated 3 CCT and 3 power selectable
Size(s) (in)		4, 6	3, 4, 6	4	3, 4	3.5	4, 5-6	4	4, 6	4, 6	4, 6, 8
Shape											
Watts (W)		11, 14	7, 9, 12	8, 9	7	12	10, 12, 15	8	7, 9	6/9/12/15 10/15/20/25	7/9/12 12/16/20 15/20/25
Lumen output (lm)		750, 1 100	Round: 500, 600, 820 Square: 450, 550, 780	Single CCT: 750 CCT Selectable: Up to 650	Warm Dim: 470 Single CCT: Up to 620	Warm Dim: 660 Single CCT: Up to 950 CCT Selectable: 850	Single CCT: 650, 850 CCT Selectable: 700, 1 100	650	550, 700	500/750/1 000/1 200 900/1 350/1 850/2 000	595/765/1 000 1 080/1 440/2 000 1 800/2 200/2 900
Volts (VAC)		120	120	120	120	120 120-277 ²	120	120	120	120-347	120-347
Color Temp. (K)	Single	3 000	2 700, 3 000, 4 000, 5 000	3 000	3 000, 4 000	3 000, 4 000	2 700, 3 000, 4 000		2 700, 3 000, 4 000		
	Warm Dim		3 000-2 200		3 000-2 200	3 000-2 200					
	Selectable	3 CCT: 2 700/3 000/4 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 2 700/3 000/4 000		5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	5 CCT: 2 700/3 000/3 500/4 000/5 000	3 CCT: 3 000/3 500/4 000	3 CCT: 3 000/3 500/4 000
Color finish											
CRI		80+	80+	90+	80+, 90+	90+	90+	80+	80+	90+	80+
Beam angle											
Location											
Dimmable		ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC 0-10V ²	ELV / TRIAC	ELV / TRIAC	ELV / TRIAC		0-10 V
Cable rated		FT4	FT4, FT6	FT4	FT4	FT6					
Warranty (year)		5	7	5	5	5	5	5	5	5	5
IC rated		✓	✓	✓	✓	✓			✓		✓
Airtight		✓	✓	✓	✓	✓	✓	✓	✓		
Other details		Available in a bulk pack of 10 units ¹			Interchangeable trims, increase flexibility and reduce inventory level Available in all-in-one kit either 3" or 4" in white	Available in individual bulk pack of 10 drivers and 10 LED modules for 2-phases job site deliveries ³		Black magnetic trim sold separately ⁴	Optional trim accessory finish White, Bronze, Silver and Black ⁴		

¹ Only available in 4" 30K white

² Only available with bulk pack option

³ Only available in 3.5" 30K white

⁴ Sold separately