

# EMERGENCY LIGHTING

## Options

*For the list of options available to a specific series, please consult its catalogue page*

Option	Description
<b>A</b>	Ammeter
<b>ACTB</b>	AC Terminal Block
<b>AT</b>	Automatic test Self-diagnostic
<b>AUD</b>	Audible Alarm
<b>AUE</b>	Audible Emergency
<b>BO</b>	Black Out Option (for special wording only)
<b>WO</b>	White Out Option (for special wording only)
<b>BD</b>	Battery Disconnect
<b>CCWH</b>	White end caps & canopy kit (RMEA only)
<b>DCTB</b>	DC Terminal Block
<b>FD6</b>	6 Circuit Fused Internal Distribution
<b>HTR</b>	Internal thermostatically controlled battery heater (specify voltage)
<b>IRT</b>	Infrared Remote Test (120/347 VAC)
<b>K5</b>	1/2" Knockout for pendant mount
<b>LCP</b>	Less Canopy

Option	Description
<b>LGD</b>	Die Cast Lens Guard
<b>LC</b>	120 VAC line cord
<b>LD</b>	Lamp Disconnect (internal)
<b>LT</b>	Remote Laser Test (contact factory)
<b>PGD</b>	Lexan Guard (separate order)
<b>VS</b>	Vandal resistant wraparound shield (RML only)
<b>MS</b>	Mounting Shelf (separate order)
<b>OBM</b>	Octagon Box Mount (line cord delete)
<b>RFS</b>	Radio Frequency Suppression (specify AC voltage)
<b>SMH</b>	Side Mounted Heads
<b>OP</b>	Special Wording
<b>TD</b>	Time Delay (specify AC voltage)
<b>TLP</b>	Twist Lock Plug (specify AC voltage)
<b>TP</b>	Tamper Proof Screws
<b>V</b>	Voltmeter
<b>WGD</b>	Wireguard (separate order)

## Glossary

Term	Description
<b>IB</b>	Self-powered for 90 minutes
<b>IB1</b>	Self-powered for 120 minutes
<b>NDC</b>	No DC backup voltage
<b>UDC</b>	Universal DC backup voltage from 6 to 24 V DC