

## FLUO LED UNDERCABINET LUMINAIRE

Designed for 120 V applications, the FLUO LED allows for a quick and easy installation as no driver is required. With its seamless appearance, the FLUO LED is the ideal replacement for traditional fluorescent undercabinet, cove lighting or task lighting. Perfect for both residential and commercial applications.



LED  
fixture



damp  
location



dimnable  
fixture



### ■ Easy ON/OFF

Available in both 3 000 and 4 000 K single color temperatures and 90 CRI for true color accuracy. The FLUO LED bars offer the convenience of an ON/OFF switch directly on each bar.

### ■ Multi use

Available from 9" to 60", the FLUO LED undercabinet luminaire will fit any type of applications including cove, shelf and task lighting. Opt for the 9" luminaire to meet needs for smaller application spaces.

### ■ Uninterrupted installation

Simple surface mount installation; each slim bar includes an end-to-end connector to create a seamless run without interruption. Up to 300 W can be daisy chained.

## At a Glance

- For an installation without interruption, use the end to end connector

- ON/OFF switch

- Up to 300 W can be daisy chained

- White aluminum housing

- Frosted lens

- Suitable for damp locations

## Accessories

Power cords, jumpers and hardwire boxes available to support the installation.



# Summary Specification Table

Order Code	Part number	Watts (W)	Volts (VCA)	Color Temp. (K) <sup>2</sup>	Lumen Output (lm) <sup>3</sup>	Efficacy (lm/W)	CRI	Life L70 (hrs) <sup>4</sup>	Beam Angle (°)	Housing finish	Lens finish	Dimmable (Yes/No)	Power Factor	THD (%)	Case qty (master)
<b>9"</b>															
68478	UCFL/9IN/120V/3W/30K/FR/WH	3	120	3 000	235	78	90	50 000	120	White	Frosted	Yes	>0.90	<15	20
68479	UCFL/9IN/120V/3W/40K/FR/WH	3	120	4 000	235	78	90	50 000	120	White	Frosted	Yes	>0.90	<15	20
<b>12"</b>															
67251	UCFL/12IN/120V/5W/30K/FR/WH/STD	5	120	3 000	360	72	90	35 000	120	White	Frosted	Yes	0.95	<15	20
67252	UCFL/12IN/120V/5W/40K/FR/WH/STD	5	120	4 000	360	72	90	35 000	120	White	Frosted	Yes	0.95	<15	20
<b>24"</b>															
67253	UCFL/24IN/120V/10W/30K/FR/WH/STD	10	120	3 000	730	73	90	35 000	120	White	Frosted	Yes	0.95	<15	20
67254	UCFL/24IN/120V/10W/40K/FR/WH/STD	10	120	4 000	730	73	90	35 000	120	White	Frosted	Yes	0.95	<15	20
<b>36"</b>															
67255	UCFL/36IN/120V/15W/30K/FR/WH/STD	15	120	3 000	1 050	70	90	35 000	120	White	Frosted	Yes	0.95	<15	20
67256	UCFL/36IN/120V/15W/40K/FR/WH/STD	15	120	4 000	1 050	70	90	35 000	120	White	Frosted	Yes	0.95	<15	20
<b>48"</b>															
67257	UCFL/48IN/120V/20W/30K/FR/WH/STD	20	120	3 000	1 450	73	90	35 000	120	White	Frosted	Yes	0.95	<15	20
67258	UCFL/48IN/120V/20W/40K/FR/WH/STD	20	120	4 000	1 450	73	90	35 000	120	White	Frosted	Yes	0.95	<15	20
<b>60"</b>															
67259	UCFL/60IN/120V/25W/30K/FR/WH/STD	25	120	3 000	1 740	70	90	35 000	120	White	Frosted	Yes	0.95	<15	20
67260	UCFL/60IN/120V/25W/40K/FR/WH/STD	25	120	4 000	1 740	70	90	35 000	120	White	Frosted	Yes	0.95	<15	20