

## DSL-L DUAL HEAD LED SECURITY LIGHT

Our DSL Security lights are CCT selectable with 3 color temperature options (3 000/4 000/5 000 K) to best suit all your commercial and residential application needs.

This dual head LED security light also features a built-in dusk to dawn sensor to provide added security at night and an integrated motion sensor that turns the lights on when motion is being detected.

Offering superior performance while improving on energy savings, this fixture is ideal for walkways, yards, driveways, patios, parking lots and loading docks.



### ■ Color Selectable

An all-in-one LED security light solution offering ultimate versatility, with the ability to change the color temperature (3 000/4 000/5 000 K) for a variety of projects and applications. An ideal solution for reducing stocking inventory.

### ■ Integrated Motion Sensor

The integrated motion sensor allows to set the lights to turn ON when motion is detected during daytime or night time adding extra security to outdoor spaces.

### ■ Dusk-to-Dawn Feature

The dusk-to-dawn function allows to turn light on at dusk and off at dawn for convenience and energy savings.

## What's DSL-L?



## Motion Sensor



Mounting at 7.2 ft above the ground allows maximum range. If the sensor is mounted above this height, the usable range is reduced.

# Specification Table

Order code	Model number	Watts		Color temp.	Lumen output	Efficacy	CRI	Life L70	Tested hours LM-80	Calculated TM21	Beam angle	BUG	LED current	Finish	Dimming	Power factor	THD (%)	Traditional equivalent		Master case qty
		(W)	(VAC)															(K) <sup>1</sup>	(lm) <sup>2,3</sup>	

## CCT Selectable

<b>69236</b>	DSL-LS1A-A-3C-BR	20	120	3 000/4 000/5 000	1 974	86 - 99	80+	>100 000	10 000	>60 000	50	B2-U1-G0	0.18	Bronze	No	>0.9	<20	2x100	2x60-75	5
<b>69237</b>	DSL-LS1A-A-3C-WH	20	120	3 000/4 000/5 000	1 974	86 - 99	80+	>100 000	10 000	>60 000	50	B2-U1-G0	0.18	White	No	>0.9	<20	2x100	2x60-75	5

<sup>1</sup> Typical color temperature range: +/- 5 %.

<sup>2</sup> Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

<sup>3</sup> Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.

<sup>4</sup> Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.