



WFC LED Full cutoff Wall Pack

Selectable color temperature (3 000/4 000/5 000 K), Power selectable, Integrated photocell and Multi-Voltage (120-347 V)



Features

- Power selectable: 25/40/60 W and 80/100 W
- 3 CCT select: 3 000/4 000/5 000 K
- Integrated Photocell that can be easily disabled
- 0-10 V dimmable
- 4 conduit entries of 1/2" on each side
- Clear Polycarbonate lens
- 120-347 V
- Ambient temperature: -40°C to +50°C
- Accessory: Back plate

Power selectable



Selectable color temperature



	Order code	
Power selection	68607	68608
1	25 W	80 W
2	40 W	100 W
3	60 W	

Order code	Model number	Watts	Volts	Color temp. (K)	Lumen output (lm)	Efficiency (lm/W)	CRI	Life L70 (hrs)	Distrib. type	Finish	Dimming	Power factor	THD (%)	Traditional equivalent (W)		Case qty (master)
		(W)	(V)											HM	SHP	
68607	WFC-PS60A3-Q-3C-BR-P	25/40/60	120-347	3 000/4 000/5 000	3 625/5 640/8 220 ¹	122-137	80	50 000	III	Bronze	Yes	≥0.9	≤20	175-400	175-250	1
68608	WFC-PS100A3-Q-3C-BR-P	80/100	120-347	3 000/4 000/5 000	11 520/14 000 ¹	123-140	80	50 000	III	Bronze	Yes	≥0.9	≤20	400-1 000	250-400	1

¹ Default programming 4 000 K.

Data is based upon tests performed in a controlled environment. Actual performance can vary depending on operating conditions. All products are subject to change or may be discontinued any time without notice.

