

YLD LED Yard Light

The YLD is an energy efficient dusk to dawn yard light. It was designed for barns and farms. It is a versatile and economic LED light source.

The YLD comes standard with a twistlock photocell and features latest in LED technology allowing the user to control the color temperature and power by using the internal field adjustable integrated switches.



■ Color and Power Selectable

An all-in-one LED Yard Light solution offering ultimate versatility, with the ability to change the color temperature (3 000/4 000/5 000 K) and lumen output for a variety of projects and applications. It is an ideal cost-effective solution for all your project needs.

■ Twistlock Photocell

Twistlock Photocell comes standard.

■ Mounting Options

It includes an installation bracket for a direct wall mount with the option of adding a 15" arm mount kit for pole and wall mounting.

Specification Table

Order code	Model number	DLC Unique ID	Watts (W)	Volts (VAC)	Color temp. (K) ¹	Lumen output (lm) ^{2,3}	Efficacy (lm/W)	CRI	Life L70 (hrs) ⁴	Tested hours LM-80 (hrs) ⁴	Calculated TM21 (hrs) ²	Beam angle (°)	Distribution type	BUG	Finish	Photo-cell ⁵	Dimming	Power factor	THD (%)	Traditional equivalent (W) MH HPS	Master case qty
------------	--------------	---------------	-----------	-------------	------------------------------	----------------------------------	-----------------	-----	-----------------------------	---------------------------------------	------------------------------------	----------------	-------------------	-----	--------	-------------------------	---------	--------------	---------	-----------------------------------	-----------------

CCT and Power Selectable Including a Twistlock Photocell

69175	YLD-PS120A-W-3C-PT	S-YOVADZ	72/96/120	120-277	3 000/4 000/5 000	10 698/ 13 334/15 680	140 - 150	80+	50 000	9 000	50 000	133	Type V	B3 U3 G3	Grey	Yes	No	0.99	0.0893	175-400	150-400	4
-------	--------------------	----------	-----------	---------	-------------------	-----------------------	-----------	-----	--------	-------	--------	-----	--------	----------	------	-----	----	------	--------	---------	---------	---

¹ Typical color temperature range: +/- 5 %.

² Lumen values are derived from photometric testing. Initial lumens range: +/- 10 %.

³ Lumen values are based on 4 000 K default programming. Please refer to the LUMEN SPECIFICATION TABLE for more details on other color temperatures.

⁴ Life hours are derived from IESNA LM-80-08 testing report and projected per IESNA TM-21-11 extrapolations.

Compatible accessories

Order code	Type
69176	15" ARM MOUNT KIT
PH0009	Shorting cap

